




Wearing the hair shirt

A retrospective on Haskell


Simon Peyton Jones
Microsoft Research, Cambridge





Haskell is 15 years old
(born FPCA 87)





Haskell is 15 years old
(born FPCA'87)

Simon is 45 years old
(born 18 Jan: POPL'58)



The primordial soup



FPCA, Sept 1987: initial meeting. A dozen lazy functional programmers, wanting to agree on a common language.

- Suitable for teaching, research, and application
- Formally-described syntax and semantics
- Freely available
- Embody the apparent consensus of ideas
- Reduce unnecessary diversity


Led to...a succession of face-to-face meetings



April 1990: **Haskell 1.0** report released
(editors: Hudak, Wadler)



Timeline



← Sept 87: kick off

← Apr 90: Haskell 1.0

← Aug 91: Haskell 1.1 (153pp)

← May 92: Haskell 1.2 (SIGPLAN Notices) (164pp)


← May 96: Haskell 1.3. Monadic I/O,
separate library report

← Apr 97: Haskell 1.4 (213pp)


← Feb 99: Haskell 98 (240pp)

← Dec 02: Haskell 98 revised (260pp)

The Book!



Haskell 98



Haskell 98

- Stable
- Documented
- Consistent across implementations
- Useful for teaching, books


Haskell
development

Haskell + extensions

- Dynamic, exciting
- Unstable, undocumented, implementations vary...



Reflections on the process



- The idea of having a fixed standard (Haskell 98) in parallel with an evolving language, has worked really well
- Formal semantics only for fragments (but see [Faxen2002])
- A smallish, rather pointy-headed user-base makes Haskell nimble. Haskell has evolved rapidly and continues to do so.

Motto: avoid success at all costs



The price of usefulness



- Libraries increasingly important:
 - 1996: Separate libraries Report
 - 2001: Hierarchical library naming structure, increasingly populated
- Foreign-function interface increasingly important
 - 1993 onwards: a variety of experiments
 - 2001: successful effort to standardise a FFI across implementations
- Any language large enough to be useful is dauntingly complex



Reflections on process



- Self-appointed committee initially, but increasingly open process: there is now no Haskell committee
- Language development by user suggestion + implementers
- Gives too much power to implementers?






Syntax



Good ideas from other languages



List comprehensions

```
[(x,y) | x <- xs, y <- ys, x+y < 10]
```

Separate type signatures

```
head :: [a] -> a  
head (x:xs) = x  
head []      = error "head of nil"
```

DIY infix operators

```
f `map` xs
```

Optional layout

```
let x = 3  
    y = 4  
in x+y
```

```
let { x = 3; y = 4 } in x+y
```




Syntactic redundancy



- Seductive idea: provide just one way of doing any particular thing
- Haskell's choice: provide multiple ways, and let the programmer decide
- Main example: "declaration style" vs "expression style"



"Declaration style"



Define a function as a series of independent equations

```
map f []      = []  
map f (x:xs) = f x : map f xs
```

sign x	x > 0	= 1
	x == 0	= 0
	x < 0	= -1



"Expression style"



Define a function as an expression

```
map = \f xs -> case xs of
                []      -> []
                (x:xs) -> map f xs
```

```
sign = \x -> if x>0 then 1
              else if x==0 then 0
              else -1
```



Fat vs thin



Expression style

- Let
- Lambda
- Case
- If

Declaration style


- Where
- Function arguments on lhs
- Pattern-matching
- Guards

SLPJ's conclusion
syntactic redundancy is a big win

Tony Hoare's comment "I fear that Haskell is doomed to succeed"



Example (ICFP02 prog comp)



Pattern
match

Guard

Pattern
guard

Conditional

Where
clause

```
sp_help item@(Item cur_loc cur_link _) wq vis
| cur_length > limit          -- Beyond limit
= sp wq vis
| Just vis_link <- lookupVisited vis cur_loc
=      -- Already visited; update the visited
      -- map if cur_link is better
if cur_length >= linkLength vis_link then
    -- Current link is no better
    sp wq vis
else
    -- Current link is better
    emit vis item ++ sp wq vis'

| otherwise -- Not visited yet
= emit vis item ++ sp wq' vis'
where
    vis' = ...
    wq   = ...
```



So much for syntax...



What is important or
interesting about
Haskell?



What really matters?



Laziness
Type classes
Sexy types



Laziness



- John Hughes's famous paper "Why functional programming matters"
 - Modular programming needs powerful glue
 - Lazy evaluation enables new forms of modularity; in particular, separating *generation* from *selection*.
 - Non-strict semantics means that unrestricted beta substitution is OK.



But...




- Laziness makes it much, much harder to reason about performance, especially space. Tricky uses of seq for effect
 $\text{seq} :: a \rightarrow b \rightarrow b$
- Laziness has a real implementation cost
- Laziness can be added to a strict language (although not as easily as you might think)
- And it's not so bad only having βV instead of β



So why wear the hair shirt of laziness?

Laziness



Laziness is jolly convenient


```
sp_help item@(Item cur_loc cur_link _) wq vis
| cur_length > limit          -- Beyond limit
= sp wq vis
| Just vis_link <- lookupVisited vis cur_loc
= if cur_length >= linkLength vis_link then
    sp wq vis
  else
    emit vis item ++ sp wq vis'

| otherwise
= emit vis item ++ sp wq' vis'
where
  vis' = ...
  wq' = ...
```

Used in
two cases

Used in
one case

Combinator libraries



Recursive values are jolly useful

```
type Parser a = String -> (a, String)

exp :: Parser Expr
exp = lit "let" <+> decls <+> lit "in" <+> exp
    ||| exp <+> aexp
    ||| ...etc...
```

This is illegal in ML, because of the value restriction

Can only be made legal by eta expansion.

But that breaks the Parser abstraction,
and is extremely gruesome:

```
exp x = (lit "let" <+> decls <+> lit "in" <+> exp
    ||| exp <+> aexp
    ||| ...etc...) x
```






The big
one....



Laziness keeps you **honest**




- Every call-by-value language has given into the siren call of side effects

- But in Haskell

`(print "yes") + (print "no")`
just does not make sense. Even worse is
`[print "yes", print "no"]`

- So effects (I/O, references, exceptions) are just not an option.

- Result: **prolonged embarrassment**.
Stream-based I/O, continuation I/O...
but NO DEALS WITH THE DEVIL



Monadic I/O




A value of type (`IO t`) is an “action**” that, when performed, may do some input/output before delivering a result of type `t`.**

eg.

```
getChar :: IO Char
putChar :: Char -> IO ()
```



Performing I/O




main :: IO a

- A program is a single I/O action
- Running the program performs the action
- Can't do I/O from pure code.
- Result: clean separation of pure code from imperative code



Connecting I/O operations




```
(>>=)  :: IO a -> (a -> IO b) -> IO b  
return :: a -> IO a
```

eg.

```
getChar    >>= ( \a ->  
getChar    >>= ( \b ->  
putChar b  >>= ( \() ->  
return (a,b) )))
```



The do-notation



```
getChar    >>= \a ->  
getChar    >>= \b ->  
putchar b  >>= \() ->  
return (a,b)
```

==

```
do {  
  a <- getChar;  
  b <- getChar;  
  putchar b;  
  return (a,b)  
}
```

- Syntactic sugar only
- Easy translation into ($\gg=$), return
- Deliberately imperative “look and feel”



Control structures



Values of type `(IO t)` are first class

So we can define our own "control structures"

```
forever :: IO () -> IO ()  
forever a = do { a; forever a }  
  
repeatN :: Int -> IO () -> IO ()  
repeatN 0 a = return ()  
repeatN n a = do { a; repeatN (n-1) a }
```

e.g. `repeatN 10 (putChar 'x')`



Monads generally



A monad consists of:

- A type constructor M
- $\text{bind} :: M\ a \rightarrow (a \rightarrow M\ b) \rightarrow M\ b$
- $\text{unit} :: a \rightarrow M\ a$
- PLUS some per-monad operations (e.g. $\text{getChar} :: \text{IO Char}$)

There are lots of useful
monads, not only I/O



Monads



- Exceptions

```
type Exn a = Either String a
fail :: String -> Exn a
```

- Unique supply

```
type Uniq a = Int -> (a, Int)
new :: Uniq Int
```


- Parsers

```
type Parser a = String -> [(a, String)]
alt :: Parser a -> Parser a -> Parser a
```

Monad combinators (e.g. sequence, fold, etc), and do-notation, work over all monads



Example: a type checker



```
tcExpr :: Expr -> Tc Type
tcExpr (App fun arg)
  = do { fun_ty <- tcExpr fun
        ; arg_ty <- tcExpr arg
        ; res_ty <- newTyVar
        ; unify fun_ty (arg_ty --> res_ty)
        ; return res_ty }
```


Tc monad hides all the plumbing:

- Exceptions and failure
- Current substitution (unification)
- Type environment
- Current source location
- Manufacturing fresh type variables

Robust to changes in plumbing



The IO monad



The IO monad allows controlled introduction of other effect-ful language features (not just I/O)

- State

```
newRef  :: IO (IORef a)
```

```
read    :: IORef s a -> IO a
```

```
write   :: IORef s a -> a -> IO ()
```

- Concurrency

```
fork     :: IO a -> IO ThreadId
```

```
newMVar  :: IO (MVar a)
```


```
takeMVar :: MVar a -> IO a
```

```
putMVar  :: MVar a -> a -> IO ()
```



What have we achieved?

- The ability to mix imperative and purely-functional programming



Imperative "skin"



What have we achieved?



- ...without ruining either
- All laws of pure functional programming remain unconditionally true, even of actions

e.g. $\text{let } x=e \text{ in } \dots x \dots x \dots$

$=$

$\dots e \dots e \dots$



What we have not achieved



- Imperative programming is no easier than it always was

e.g. `do { ...; x <- f 1; y <- f 2; ...}`


`?=?`

`do { ...; y <- f 2; x <- f 1; ...}`

- ...but there's less of it!
- ...and actions are first-class values



Open challenge 1



Open problem: the IO monad has become Haskell's sin-bin. (Whenever we don't understand something, we toss it in the IO monad.)

Festering sore:

`unsafePerformIO :: IO a -> a`

Dangerous, indeed type-unsafe, but occasionally indispensable.


Wanted: finer-grain effect partitioning

e.g.

`IO {read x, write y} Int`



Open challenge 2



Which would you prefer?

```
do { a <- f x;  
    b <- g y;  
    h a b }
```

```
h (f x) (g y)
```

In a commutative monad, it does not matter whether we do `(f x)` first or `(g y)`.

Commutative monads are very common. (Environment, unique supply, random number generation.) For these, monads over-sequentialise.

Wanted: theory and notation for some cool compromise.



Monad summary



- Monads are a beautiful example of a theory-into-practice (more the thought pattern than actual theorems)
- Hidden effects are like **hire-purchase**: pay nothing now, but it catches up with you in the end
- Enforced purity is like **paying up front**: painful on Day 1, but usually worth it
- But we made one big mistake...



Our biggest mistake



Using the scary term
"monad"
rather than
"warm fuzzy thing"



What really matters?



~~Laziness~~

Purity and monads

Type classes

Sexy types



SLPJ conclusions



- Purity is more important than, and quite independent of, laziness
- The next ML will be pure, with effects only via monads
- Still unclear exactly how to add laziness to a strict language. For example, do we want a type distinction between (say) a lazy Int and a strict Int?






Type classes



Type classes



Initially, just a neat way to get systematic overloading of `(==)`, `read`, `show`.

```
class Eq a where
  (==) :: a -> a -> Bool

instance Eq Int where
  i1 == i2 = eqInt i1 i2

instance (Eq a) => Eq [a] where
  []      == []      = True
  (x:xs) == (y:ys) = (x == y) && (xs == ys)

member :: Eq a => a -> [a] -> Bool
member x []                = False
member x (y:ys) | x==y     = True
                 | otherwise = member x ys
```



Implementing type classes

```
data Eq a = MkEq (a->a->Bool)
eq (MkEq e) = e
```

```
dEqInt :: Eq Int
dEqInt = MkEq eqInt
```

```
dEqList :: Eq a -> Eq [a]
dEqList (MkEq e) = MkEq el
  where el [] [] = True
        el (x:xs) (y:ys) = x `e` y && xs `el` ys
```

```
member :: Eq a -> a -> [a] -> Bool
member d x [] = False
member d x (y:ys) | eq d x y = True
                  | otherwise = member deq x ys
```


Instance
declarations create
dictionaries

Class witnessed
by a "dictionary"
of methods


Overloaded
functions
take extra
dictionary
parameter(s)

Type classes over time

- Type classes are the most unusual feature of Haskell's type system



Type classes are useful



Type classes have proved extraordinarily convenient in practice


- Equality, ordering, serialisation, numerical operations, *and not just the built-in ones (e.g. pretty-printing, time-varying values)*
- Monadic operations

```
class Monad m where
  return :: a -> m a
  (>>=)  :: m a -> (a -> m b) -> m b
  fail   :: String -> m a
```

Note the higher-kinded type variable, m



Quickcheck



```
propRev :: [Int] -> Bool
propRev xs = reverse (reverse xs) == xs

propRevApp :: [Int] -> [Int] -> Bool
propRevApp xs ys = reverse (xs++ys) ==
                    reverse ys ++ reverse xs
```

```
ghci> quickCheck propRev
OK: passed 100 tests
```


```
ghci> quickCheck propRevApp
OK: passed 100 tests
```

Quickcheck (which is just a Haskell 98 library)

- Works out how many arguments
- Generates suitable test data
- Runs tests



Quickcheck



```
quickCheck :: Test a => a -> IO ()

class Test a where
  prop :: a -> Rand -> Bool

class Arby a where
  arby :: Rand -> a

instance (Arby a, Test b) => Test (a->b) where
  prop f r = prop (f (arby r1)) r2
             where (r1,r2) = split r

instance Test Bool where
  prop b r = b
```




Extensibility



- Like OOP, one can add new data types "later". E.g. QuickCheck works for your new data types (provided you make them instances of **Arby**)
- ...but also not like OOP



Type-based dispatch



```
class Num a where
  (+)          :: a -> a -> a
  negate      :: a -> a
  fromInteger :: Integer -> a
  ...
```


- A bit like OOP, except that method suite passed separately?

```
double :: Num a => a -> a
double x = x+x
```

- No: type classes implement **type-based** dispatch, not **value-based** dispatch



Type-based dispatch



```
class Num a where
  (+)          :: a -> a -> a
  negate      :: a -> a
  fromInteger :: Integer -> a
  ...
```

```
double :: Num a => a -> a
```

```
double x = 2*x
```

means


```
double :: Num a -> a -> a
```

```
double d x = mul d (fromInteger d 2) x
```

The overloaded value is *returned by* *fromInteger*, not passed to it. It is the dictionary (and type) that are passed as argument to *fromInteger*



Type-based dispatch



So the links to intensional polymorphism are much closer than the links to OOP.

The dictionary is like a proxy for the (interesting aspects of) the type argument of a polymorphic function.

f :: forall a. a -> Int

f t (x::t) = ...typecase t...

Intensional
polymorphism

f :: forall a. C a => a -> Int

f x = ... (call method of C) ...

Haskell



C.f. Crary et al λR (ICFP98), Baars et al (ICFP02)

Cool generalisations



- Multi-parameter type classes
- Higher-kinded type variables (a.k.a. constructor classes)
- Overlapping instances
- Functional dependencies (Jones ESOP'00)
- Type classes as logic programs (Neubauer et al POPL'02)



Qualified types



- Type classes are an example of **qualified types** [Jones thesis]. Main features
 - types of form $\forall \alpha. Q \Rightarrow \tau$
 - qualifiers Q are witnessed by run-time evidence
- Known examples
 - **type classes** (evidence = tuple of methods)
 - **implicit parameters** (evidence = value of implicit param)
 - **extensible records** (evidence = offset of field in record)
- Another unifying idea: Constraint Handling Rules (Stucky/Sulzmann ICFP'02)



Type classes summary



- A much more far-reaching idea than we first realised
- Variants adopted in Isabel, Clean, Mercury, Hal, Escher
- Open questions:
 - tension between desire for overlap and the open-world goal
 - danger of death by complexity






Sexy types



Sexy types



Haskell has become a laboratory and playground for advanced type hackery

- Polymorphic recursion
- Higher kinded type variables
`data T k a = T a (k (T k a))`
- Polymorphic functions as constructor arguments
`data T = MkT (forall a. [a] -> [a])`
- Polymorphic functions as arbitrary function arguments (higher ranked types)
`f :: (forall a. [a] -> [a]) -> ...`
- Existential types
`data T = exists a. Show a => MkT a`



Is sexy good? Yes!



- Well typed programs don't go wrong
- Less mundanely (but more allusively) sexy types let you think higher thoughts and still stay [almost] sane:
 - deeply higher-order functions
 - functors
 - folds and unfolds
 - monads and monad transformers
 - arrows (now finding application in real-time reactive programming)
 - short-cut deforestation
 - bootstrapped data structures



How sexy?



- Damas-Milner is on a cusp:
 - Can infer most-general types without any type annotations at all
 - But virtually any extension destroys this property
- Adding type quite modest type annotations lets us go a LOT further (as we have already seen) without losing inference for most of the program.
- Still missing from the sexiest Haskell impls
 - λ at the type level
 - Subtyping
 - Impredicativity



Destination = $F^w_{<:}$



Open question

What is a good design for user-level type annotation that exposes the power of F^w or $F^w_{<:}$, but co-exists with type inference?


C.f. Didier & Didier's MLF work



Modules

ML functors

Difficulty



Power




Porsche

High power, but poor power/cost ratio

- Separate module language
- First class modules problematic
- Big step in compiler complexity
- Full power seldom needed

ML functors



Haskell 98

Haskell + sexy types

Ford Cortina with alloy wheels

Medium power, with good power/cost

- Module parameterisation too weak
- No language support for module signatures




Modules



- Haskell has many features that overlap with what ML-style modules offer:
 - type classes
 - first class universals and existentials
- Does Haskell need functors anyway? No: one seldom needs to instantiate the same functor at different arguments
- But Haskell lacks a way to distribute “open” libraries, where the client provides some base modules; need module signatures and type-safe linking (e.g. PLT, Knit?). π not λ !
- **Wanted: a design with better power, but good power/weight.**



Encapsulating it all



```
data ST s a    -- Abstract
newRef :: a -> ST s (STRef s a)
read  :: STRef s a -> ST s a
write :: STRef s a -> a -> ST s ()
```

```
runST :: (forall s. ST s a) -> a
```


Stateful
computation

Pure result

```
sort :: Ord a => [a] -> [a]
sort xs = runST (do { ..in-place sort.. })
```



Encapsulating it all



```
runST :: (forall s. ST s a) -> a
```

Higher rank type

Security of
encapsulation
depends on
parametricity

Monads

And that depends on type
classes to make non-parametric
operations explicit
(e.g. $f :: \text{Ord } a \Rightarrow a \rightarrow a$)

Parametricity depends on there
being few polymorphic functions
(e.g.. $f :: a \rightarrow a$ means f is the
identity function or bottom)

And it also depends
on purity (no side
effects)



Shirts off to Wadler



Type classes

"Making ad hoc polymorphism less ad hoc" [POPL89]

Monads

"The essence of functional programming" [POPL92]

Sexy types

"Theorems for free" [FPCA89]



The Haskell committee



Arvind
Lennart Augustsson
Dave Barton
Brian Boutel
Warren Burton
Jon Fairbairn
Joseph Fasel
Andy Gordon
Maria Guzman
Kevin Hammond
Ralf Hinze
Paul Hudak [editor]
John Hughes [editor]

Thomas Johnsson
Mark Jones
Dick Kieburtz
John Launchbury
Erik Meijer
Rishiyur Nikhil
John Peterson
Simon Peyton Jones [editor]
Mike Reeve
Alastair Reid
Colin Runciman
Philip Wadler [editor]
David Wise
Jonathan Young

